


Flexo F6



- **Easy, Cost & Labor Effective Installation**
- **More Flexible Than Split Convuluted or Spiral Wrap**
- **Soft and Quiet In High Vibration Uses**
- **25% Edge Overlap**
- **Cut & Abrasion Resistant**
- **Chemically Inert**
- **Halogen Free**
- **Retains Shape and Rigidity Throughout -75°C to 125°C Temperature Range**
- **Melt Temp 230°C**



The large overlap allows easy installation over splices and inline connectors without exposing wires and cables.



The split design and open braid construction make F6 perfect for large network installations that require frequent access.

Flexible, Semi-Rigid Wrappable Split Braided Tube

F6's unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance. The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners (velcro, tape, etc.)

The 10 mil PET braid is lightweight, quiet and flexible. The 25% edge overlap (at nominal diameter) allows coverage around inline plugs, connectors and splices.

F6 will bend to a tight radius without distorting or splitting open and, unlike full rigid tubing, will not impair or affect the flexibility of harnesses.



Nominal Size	Part #	Expansion Range		Bulk Lengths	Minimum Cuts	Available Colors	Lbs/100'
		Min.	Max.				
1/8"	F6N0.13	NA	NA	400'	100'	Black	0.2
1/4"	F6N0.25	NA	NA	200'	100'	Black	0.6
1/2"	F6N0.50	NA	NA	150'	75'	Black	1.4
3/4"	F6N0.75	NA	NA	100'	50'	Black	1.6
1"	F6N1.00	NA	NA	100'	50'	Black	2.0
1 1/2"	F6N1.50	NA	NA	75'	25'	Black	2.7
2"	F6N2.00	NA	NA	50'	25'	Black	3.6

